CLIPPER CHARGER



Engineered around a central pivoting front axle, ContourDTS allows the front axle of the mower to rotate horizontally, absorbing bumps & imperfections, offering a smoother - more comfortable ride. As terrain changes, the pivoting axle keeps all 4 tires on the ground for maximum traction. The deck is independently suspended from each side of the pivoting front axle, guided by each front wheel. This allows each side of the deck to independently track to the contour of the ground, preventing dipping & scalping for an unrivaled quality of cut.

Access

The Charger is equipped with our stand-up deck. It has never been easier to access the underside of the deck for cleaning and maintenance. This also gives you easy access to the spindles, which are field serviceable so you can get back to moving quickly.

Stability

The Charger is designed with the fuel tank under the seat for stability and protection. This provides a low center of gravity, which, along with wide rear tires, provides better traction and steadiness on slopes. The Charger also comes standard with ROPS (Roll Over Protection System) and seat belt for added safety.

COUNTRY CLIPPER ZERO TURN MOWERS

CHARGER

Innovative Deck Design

Stand-Up Deck

- · Easy Access to Underside of Deck for Maintenance and Cleaning
- No Tools Needed
- Process Takes Less Than 60 Seconds

Rugged Deck Construction

- · Welded 10 Gauge Steel Shell
- Reinforced with 10 Gauge Steel Plates
- 3/8" Wear Guard on Trim Edge
- Protective Bullnose on Leading Edge of Deck
- High Impact Anti-Scalp Rollers

Industry Proven Steering

Joystick Steering

- Exclusive to Country Clipper Mowers
- · Leaves You with a Free Hand
- Easy to Learn
- Fun to Use!

 Twin Lever Steering

Learn more at CountryClipper.com

Accessories

- Bagger
- Mulch Kit
- Hitch Kit
- Hand Jack
- Push BladeLight Kit

Hand Rail

Power Lift Kit

	25552KAJ-1055 & 25552KAT-1055	25560KAJ-1055 & 25560KAT-1055	
Engine	Kawasaki FX801V		
Horsepower	25.5		
Fuel Capacity	7 Gallon		
Drive System	Hydro-Gear 12 cc Pumps & Parker Wheel Motors		
Rear Tires	24 x 12 - 12		
Front Tires	13 x 6.5 - 6		
Speed	10.5 mph		
Cutting Width	52"	60"	
Blade Length	18 3/8"	21"	
Cutting Height	2" - 5" (Adjusted in 1/4" increments)		
Length	84"		
Width (with chute)	65"	73"	
Weight (Approx.)	1081 lbs	1096 lbs	
Standard Features	Electric Start, Arm Rest, Cup Holder, Hour Meter, Front Step, ContourDTS™, ROPS		

Due to continuous product improvement, specifications are subject to change without notice.

- Commercial Use -

First 2 years Parts & Labor 3rd year Blade Spindle & Frame/Deck Weldment 4th & 5th year Frame & Deck Weldment

- Residential Use -

First 2 years Parts & Labor 3rd year Parts 4th & 5th year Frame & Deck Weldement Residential or Commercial

	Commercial	
Hydro-Gear Drive	2 year Ltd	
Kohler Engines	3 year Ltd	
Kawasaki Engines	3 year Ltd	

See Warranty Statement for Complete Details

_	B 4		
⊢∩r	N/IOre	Inform	ıatı∩n:
1 01	IVIOIC		iation.